




CVC6246iHR 2.8 - 12mm auto iris varifocal lens, dark grey housing
CVC6246iHRW 2.8 - 12mm auto iris varifocal lens, white housing



Features

- 650 lines of color resolution
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Minimum illumination 0.00002 lux (Intensifier™ @ 512x)
- Full OSD operation
- Wall or ceiling mount
- S/N Ratio more than 52dB (weight on)
- EZ mount system simplifies installation
- 5 year warranty

Now with Presets:
 Outdoor, Indoor, Elevator,
 Lobby, Hallway & Dark



Specifications

| | | | |
|--------------------------------|--|----------------------------|---|
| Image Sensor | 1/3" Sony Super HAD II™ CCD | White Balance | ATW / Outdoor / Indoor / Manual / AWC (1,700°K - 11,000°K) |
| Resolution | 650 TV lines | Intensifier™ | Auto / Off (selectable x2 - x512) |
| Minimum Illumination | CDS Off: 0.15 lux CDS On: 0.00002 lux | Motion Detection | On / Off (8 programmable zones) |
| Total Pixels | 811 (H) x 508 (V) | Privacy Masking | On / Off (12 programmable zones) |
| Effective Pixels | 768 (H) x 494 (V) | Speco DNR..... | On / Off (level adjustable) |
| TV System..... | NTSC, PAL | Digital Zoom | On / Off (1x - 16x) |
| Scanning Frequency | 15.734kHz (H) & 59.94Hz (V) | DIS | On / Off |
| Scanning System | 2:1 interlace | Sharpness | On / Off (level adjustable) |
| Synchronization | Internal | Flip / Mirror | On / Off |
| S/N Ratio | More than 52dB | Power Supply | 12VDC / 24VAC (dual voltage) (power supply not included) |
| Video Output | CVBS: 1.0Vp-p / 75 Ohm | Power Consumption | 12VDC, 250mA / 24VAC, 100mA |
| Electronic Shutter Speed | 1/60 sec. - 1/120,000 sec. | Operating Temperature..... | 14° F - 122° F |
| OSD | Available | Storage Temperature..... | -4° F - 140° F |
| WDR | On / Off (level adjustable) | Dimensions..... | 3.82" (H) x 5.47" (Dia.) |
| Backlight Compensation..... | BLC / HLC / Off | Weight | 1.54 lbs. |
| Day & Night | Color / BW / Auto | | |
| Gain Control | High / Low / Off | | |

Optional Mounting Accessories



DFM Series
 Tile ceiling flush
 mount accessory



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 10/26/11

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com