

CVC6146HR



High Resolution Color Dome Camera with 2.8-11mm Auto Iris Lens **CVC6146HR**



*Optional
Mounting
Accessories
Available:*



7246WMT
Wall Mount for
Dome Cameras
(Sold Separately)



BCP
Corner/Pole Mount
for Dome Cameras
(Sold Separately)



DFM1 / DFM2
Recessed Mounts
for Dome Cameras
(Sold Separately)

Specifications

Resolution	550 lines
Image Device	1/3" Sony Super-HAD™ CCD
Min. Object Illumination	0.3 lux sensitivity
Electronic Shutter	1/60-1/100,000 seconds
DIP Switches	BLC, FLK, AGC AND AES/AI
Built In Lens	2.8-11mm F1.4 auto iris lens
Video S/N Ratio	Greater than 48dB
Gamma	0.45
Mechanical Construction	Polycarbonate housing with lined dome cover
Video Signal Output	Composite Video, 1 Vp-p into 75 Ohms, test connection
Power Consumption	300mA (DC) / 4W (AC)
Power Requirement	Dual voltage operation: 12V DC & 24V AC
Scanning System	525 lines interlaced
Synchronization	Internal / line locked in 24V AC mode
Operating Environment	14°F to 122°F
Dimensions	5.5" Dia. x 3.5" H
Weight	12 oz.
Accessories	Wall/ceiling mountable with 3-axis mount & template included

Speco Technologies is constantly developing product improvements.
We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 4/28/10

For more information contact us at:
Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880